

Standard Lift Station										
Tank Material										
-PP	Polypropylene									
-PE	Polyethylene (7-30 gallon only)									
-PF	PVDF									
Pump Configurations										
-S	Simplex (Single Pump)									
-D	Duplex (Dual Pump)									
Tank Volume (Gal.)										
-7	7-Gallon									
-11	11-Gallon									
-15	15-Gallon									
-30	30-Gallon									
-50	50-Gallon									
-115	115-Gallon									
-200	200-Gallon									
-260	260-Gallon									
Flow Rate (Max GPM)										
-XX	Flow Range (Max GPM)									
TDH (FT)										
-XX	TDH (FT)									
Plumbing Materials										
-CV	CPVC									
-PP	Polypropylene									
-PF	PVDF									
Voltages										
-120	120VAC, 60Hz, Single Phase									
-208	208VAC, 60Hz, Single Phase									
-230	230VAC, 60Hz, Three Phase									
-460	460VAC, 60Hz, Three Phase									
Pump Technologies										
-V	Vertical Centrifugal									
-SP	Self-Priming Horizontal Centrifugal									
-S	Submersible									
-AOD	AODD									
Containment										
-L/-LS	Leak Pan/Leak Switch									
-X	No Leak Containment									
-SPX	-PP	-S	-7	-50	-50	-CV	-120	-V	-L/-LS	Example Code